



Epson SureColor F10060/10060H

- Compact and cost effective fabric / soft signage production at up to 255 m²/hr
- Supports roll based manufacturing on media up to 76" (1950 mm) wide
- Epson UltraChrome® DS ink enables an exceptional gamut using just 4 colours
- Enhanced 6c F10060H model enables operation with added LcLm or Fluorescent ink
- Advanced platen, high precision feed management and take-up systems for efficient high quality roll-to-roll production on the widest range of media
- Latest Epson PrecisionCore[™] print heads for outstanding results at the highest speeds
- Heavy roll support and dual 40/60 L bulk ink supply system with hot swap
- Oeko-Tex[™] certification ensures fabric is safe for adults, children & infants¹
- Supplied with Epson Edge Print and Epson Accounting Tool software
- New Epson Cloud Solution PORT remote monitoring, reporting & management
- Comprehensive and flexible service with cover extendable up to FIVE years complete with optional User Self Replacement of selected key components including print heads³

Epson SureColor Fabric Range SC-F10060/H 76" High Speed Roll Based Dye Sublimation

Product Specifications			
PRINT TECHNOLOGY		PHYSICAL	
Drivet Hood	4 x 4.7" PrecisionCore [™] Micro TFP (6 with F10060H) with auto-alignment, advanced Variable Sized Droplet & Precision Dot Technology, ink-less nozzle status monitoring, auto recovery & self cleaning, supports optional User Self Replacement³	Dimensions (WxHxD) & Weight (with MSS & CISS, no ink)	F10060: 4,607 x 1,886 x 1,303 mm, 736 Kg F10060H: 5,008 x 1,886 x 1,303 mm, 767 Kg
Print Head		Packaging	F10060 Printer & Dryer: 3.9 x 1.9 x 1.2 m, 903 kg F10060 Media & Ink System: 3.9 x 1.2 x 1.4 m, 330 kg F10060H Printer & Dryer: 3.9 x 1.9 x 1.2 m, 924 kg F10060H Media & Ink System: 3.9 x 1.2 x 1.4 m, 354 kg
Print Modes	Uni & Bi-directional		
Configuration	1,600 x 2 nozzles per colour		1 Toodon Modia & link dystoni. 6.5 X 1.2 X 1.4 III, 664 Ng
Max Resolution	1,200 x 1,200 dpi	CONFIGURATIONS & OPTIONS ^{2&3}	
Min Droplet Size	3.8 pl	SCF100601Y	4c Printer with CoverPlus 1YR on-site service
INK SYSTEM		SCF100603Y	4c Printer with CoverPlus 3YR on-site service
Ink Family	Epson Ultrachrome® DS	SCF100605Y	4c Printer with CoverPlus 5YR on-site service
Ink Type	Dye Sublimation (High Density Black)	SCF10060HL1Y	6c LcLm Printer with CoverPlus 1YR on-site service
Supply	Dual 3/10 L with hot swap (F10060: CYMK, F10060H: CYMKLcLm or CYMKFyFp)	SCF10060HL3Y	6c LcLm Printer with CoverPlus 3YR on-site service
		SCF10060HL5Y	6c LcLm Printer with CoverPlus 5YR on-site service
PERFORMANCE F10060 F10060H ⁴		SCF10060HF1Y	6c FyFp Printer with CoverPlus 1YR on-site service
Fast Fabric	255 I 246 m ² /hr 1.1 Pass (300 x 600 dpi)	SCF10060HF3Y	6c FyFp Printer with CoverPlus 3YR on-site service
Apparel	150 I 144 m²/hr 2.1 Pass (600 x 600 dpi)	SCF10060HF5Y	6c FyFp Printer with CoverPlus 5YR on-site service
Soft Signage	103 99 m²/hr 3.1 Pass (600 x 600 dpi)	CONSUMABLES	
MEDIA SUPPORT		C13S210071	Replacement Waste Tank
Format (Single Roll)	250 mm max diameter, 60 kg max weight, 1 mm max thick, 300~1950 mm width (914.4~1950 mm for roll to roll operation)	C13S210065	Replacement Head Wiper Roll
		C13S210103	Cleaning Kit
Print Margins (min)	3 mm L/R (7 mm with edge guides), 5 mm Top/ Bottom	C13S090013	Cleaning Sticks
OPERATION		C12C890891	Cleaning Wipes
Control Panel	9" Colour LCD with in-built help	C13T43B140~440	3 L CYMK UltraChrome Ink Boxs
Included Software	Comms Driver, EpsonNet Setup, EpsonNet Config & Print	C13T43B540/640	3 L Lc/Lm UltraChrome Ink Boxs
	utilities, Epson Edge Dashboard, Accounting Tool, Epson Edge Print Pro, & Cloud Solution PORT	C13T43B740/840	3 L Fy/Fp UltraChrome Ink Boxs
Interface	USB 3.0 & Ethernet/ 1000Base-T	C13T43H140~440	10 L CYMK UltraChrome Ink Boxs
Memory	155 GB	C13T43H540/640	10 L Lc/Lm UltraChrome Ink Boxs
Media Dryer	Dual front & back with adjustable temp: 0~110°C	C13T43H740/840	10 L Fy/Fp UltraChrome Ink Boxs
ENVIRONMENTAL		WHAT'S IN THE BOX ⁵	
Operational Temp	10~35°C (18~28°C recommended)	Printer with Auto Take Up, Dryer and Ink Supply System, 3 L Ink Set, 1 x reusable 4 L Waste Tank, 1 x Head Wiper Roll, 1 x Cleaning Kit, 1 Roll of Epson Transfer Paper, Utility s/w & User manual (CD), Epson Edge Print Pro & Accounting s/w (web download)	
Operational Humidity	20~80% (no condensation, 40 ~ 60% recommended)		
Power Supply	2 X 16 A 220 V ~240 V, 50 HZ - 60 HZ		
Power Consumption	F10060: 3.9 KW Operating / 221 W Standby F10060H: 4.4 KW Operating / 230 W Standby	Epson dye sublimation inks used in this printer meet the needs of Oeko-Tex Eco Passport safety standard when applied and affixed to appropriate fabric. For further details on this standard please consult www.oeko-tex.com/ecopassport	
	2. The printer is qualified with a 90 day warranty course the		control or one the exist mechanism (seekuling point beeds) and introduced The manager is a consented



Operating Noise

Operating Space



- For further details on this standard please consult www.oeko-tex.com/ecopassport

 The printer is supplied with a 90 day warranty. The warranty covers the print mechanism (including print heads) and ink system. The warranty is augmented with a selectable period of CoverPlus on-site service. Free on-site repair is provided in major metro locations (non-metro locations will attract an additional travelling charge). Service is conditional on a range of factors including appropriate product usage, operation within print life limits, regular & appropriate
- user maintenance, use of correct and Genuine Epson consumables, agreement and registration under Epson Cloud Solution PORT.

 3. User replacement of selected components is supported on this model conditional on registration under Epson Cloud Solution PORT and training of operators
- 4 Performance in the searchest components is supported in this induction times will vary depending on a range of factors including point mode, computing platform, print application/RIP, file type/ format/size, networking, and sublimation method. Effective resolution with Half Tone application is 300 x 300 dpi.
- 5 Ink and media may be supplied in additional boxes. Operation will require installation of an appropriate power supply and connection to a network with Internet access. The independent sourcing of a calendar press will generally also be required. Some software components will need to be downloaded from the appropriate Epson Website. Important: not all software is Mac compatible (check website for details).






5.6 x 3.3 x 2.1 m (WxDxH Recommended)









Superior imaging with extended gamut and high colour accuracy

Heavy roll support with active intelligent feed management

Compact double-sided drying system

Advanced media set-up with

Integrated head wiper with user replaceable fabric roll.

Ink Supply System holds up to 80 L with automatic hot-swap

Better Products for a Better Future

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. All print samples shown herein are simulations. **IMPORTANT: This document contains simplified specifications with all content subject to change; for full and latest information please see the relevant Epson website.** V2.2 July 2021

EPSON AUSTRALIA

Level 1, 3 Talavera Road North Ryde NSW 2113 Tel: (02) 8899 3666 www.epson.com.au ABN 91 002 625 783

EPSON NEW ZEALAND

Level 2, 7-9 Fanshawe Street Auckland, 1010 (09) 366 6855 www.epson.co.nz



