



## Epson SureColor F2260 DTG / DTF

- Direct-to-garment (DTG) and direct-to-film DTFilm printer
- New UltraChrome® DG2 ink for improved imaging on fabric and film
- Pouch-based ink supply for reduced production cost with less waste
- Latest Epson high-performance PrecisionCore MicroTFP printhead
- Efficient operation with auto height adjustment, frame and frame-less loading
- Quiet fan-less operation with self-cleaning printhead and capping system
- Supplied with upgraded Epson Garment Creator 2 application software
- Garments produced with this printer are suitable for use by all ages
- Improved ergonomics for easier installation and more efficient operation
- Comprehensive 'heads-and-all' warranty with service cover extendable up to five years and supported by Epson Cloud Solution PORT<sup>1</sup>

## **Epson SureColor Fabric Range** SC-F2260 Desktop DTG/DTF Printer

		•	
<b>Product Specificati</b>	ions		
PRINTING TECHNOLOGY		WHAT'S IN THE BOX⁵	
Printhead	Epson 1.33" PrecisionCore® MicroTFP™	Printer, power cord, 1 x set 800 ml pouches, 20 litre pre-treat solution, medium hanger	
Print Modes	Uni & Bi-directional	platen and grip pad, waste tank, maintenance kit and head cleaning set, set up guide. All	
Configuration	400 Nozzles x 8 lines	software delivered via web download. On-line manual with help. On-line PORT service.	
Maximum Resolution	1200 x 1200 dpi	CONFIGURATION OPTIONS <sup>1</sup>	
Minimum Droplet Size	12.8 pl	SCF2260W1Y	Printer with 1Yr On-Site Wty
INK SYSTEM	·	SCF2260W3Y	Printer with 1Yr On-Site Wty + 2Yr CoverPlus
Ink Type	Epson UltraChrome® DG2	SCF2260W5Y	Printer with 1 Yr On-Site Wty + 4Yr CoverPlus
Standard Configuration	CYMK + Dual White + Maint Liquid	OPTIONAL ACCESSORIES	
Loading	800 ml x 7 pouches, front tray system	C12C938911	Large Hanger Platen
PERFORMANCE <sup>2</sup>		C12C938991	Grooved Platen (for shirts with buttons or a zipper)
Standard Configuration	Clr + Wht: 89s Fast / 142s Prodn / 321s Quality	C12C938931	Medium Hanger Platen
	Wht Only: 52s Fast / 86s Prodn / 213s Quality	C12C939031	Small Hanger Platen
	Clr Only: 28s Fast / 43s Prodn / 128s Quality)	C12C933951	Extra Small Platen
MEDIA SUPPORT <sup>3</sup>	,	C12C939051	Sleeve Platen
DTFilm Production	Various film & power combinations	CONSUMABLES	
DTG Production	Cotton, polyester and mixed fibre garments	C13T54R900	800 ml Cleaning Liquid
Max Thickness / Weight	27 mm / 1.5 kg per garment	C13T54LB00	800 ml Maintenance Liquid
Max Print Area	Large Platen: 406 x 508 mm	C13T54L100~400, A00	800 ml ink pouches (K/C/M/Y,Wh)
	Medium & Grooved Platen: 335 x 406 mm	C13T43R100	20 L Cotton pre-treatment liquid (concentrate)
OPERATION		C13T43R200	18 L Polyester pre-treatment liquid
Control Panel	4.3" Colour touch LCD with USB print support <sup>4</sup>	C13S400216	Head Cleaning Set kit
Utility Software	Epson Edge Dashboard, communications driver,	C13T736200	Maintenance Kit
	s/w & f/w updater, EpsonNet set-up, config & print	C13S210118	Large Hanger Platen grip pad
Application Software	Epson Garment Creator 2 & Cloud Solution PORT	C13S210119	Medium Hanger Platen grip pad
Interface	High Speed USB 2.0 and Ethernet 1000 Base-T	C13S210120	Small Hanger Platen grip pad
Memory	1GB		numable components including printheads when the printer is operated and maintained
ENVIRONMENTAL			throme DG2 ink. Cover can be extended up to a maximum total of 5 years through wided for limited areas across Australia and New Zealand with CoverPlus conditional on
Operational Temp	10-35°C	activation and connection of the printer to Epson Cloud Solution PORT. Please see relevant web site for full details.	
Operational Humidity	20 to 80% (no condensation	<sup>2</sup> Figures are print speeds only based on an image 254 x 203 mm in landscape; actual production times will depend on workflow,	
Power Supply	AC 240 V 1.6 A, 50 Hz - 60 Hz	material selection, production process, print mode, equipment settings, computing platform, file format/size and networking.  3 Optimum DTG results will be achieved on garments with a moderate to loose weave and 50% or more natural fibre content. With	
Power Consumption	46 W Operating / 30 W Standby / 7 W Sleep	the application of appropriate pre-treatment a wide range of single and mixed fibre fabrics garments can be supported however print	
Operating Noise	37 dB	adhesion and wash durability will vary. DTFilm is generally recommended for material with tight weave &/or elevated levels of synthetic content. Special care should be taken with fabrics that have been coated to repel dust &/or moisture. In all cases it is recommended	
PHYSICAL			y and wash/wear durability used prior to commencement of production.

981 mm x 499 mm x 1361 mm (WxHxD), 95 kg

1434 mm x 897 mm x 1209 mm (WxHxD), 148 kg

## d cleaning set, set up guide. All help. On-line PORT service. Site Wty + 2Yr CoverPlus Site Wty + 4Yr CoverPlus hirts with buttons or a zipper)

4 Images must be pre-processed through Garment Creator and stored on a USB device no larger than 2 TB in FAT-32 format

5 The DTG and DTFilm process requires use of a heat press while DTF requires additional use of appropriate film and powder (an



Rapid loading with tool-less macro and auto fine height adjustment



All front loading design with costeffective pouch-based ink



Upgraded Epson Garment Creator 2 software for Macintosh® & Windows®



Printer (without ink)

Shipping Carton (Main Unit)





Epson, SureColor, UltraChrome and PrecisionCore are registered trademarks of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners; Epson disclaims any and all rights in those marks. Any print samples shown herein are simulations. Specifications are subject to change without notice with customers advised to check the relevant Epson web site for latest details prior to making a purchase decision. V1.0 June 2023

Epson Australia Pty Ltd Level 1, 3 Talavera Road Macquarie Park NSW 2113 Tel: 02 8899 3666 www.epson.com.au

**Epson New Zealand** Level 2, 9 Fanshawe Street Auckland 1010 Tel: 09 366 6855 www.epson.co.nz

