



Epson SureColor F6460/6460H DS Printers

- Designed for custom clothing, soft signage, hard signage and décor
- Rapid production with cost-effective bulk ink and roll media
- Super-fast 4c model with enhanced gamut and gradation
- Super-quality 6c model with a choice of additional LcLm for max gradation, OrVi for max gamut or FyFp for max brightness
- Epson Ultrachrome[™] dye sublimation ink ensures predictable performance with superior image quality and exceptional wash/UV durability
- Uses cost-effective mess-free 1.6L ink pouches with fast spindle-less roll loading, convenient 4.3" touchscreen control and optional auto take-up
- Oeko-Tex[™] compliant so garments can be worn by adults, children and infants
- Comprehensive single source warranty with on site cover up to FIVE years¹
- Supplied with powerful Epson Edge Print PRO software and backed with advanced management and support via Epson Cloud Solution PORT

Epson SureColor Fabric F6460/6460H 4c & 6c 44" Dye Sublimation Printers

PHYSICAL (WxDxH) Dimensions

Product Specifications

PRINTING TECHNOLOGY	
Print Head	1.33" MicroPiezo TFP [®] with VSDT [®]
Print Modes	Uni & bi-directional
Nozzle Configuration	4 x 800 (F6460) / 6 x 400 (F6460H)
Maximum Resolution	1200 x 600 dpi
INK SYSTEM	
Ink Type	Epson Ultrachrome [®] DS DS/DS6 (extended)
Ink Set	4c F6460 HDkCYM
	6c F6460 HDkCYM + LcLm or OrVi or FyFp
Storage	1.6L x 4 (F6460) / 1.6L x 6 (F6460H)
PRINT PERFORMANCE ²	
Fast Fabric	53.5 m2/hr (F6460) / 38.8 m2/hr (F6460H)
Production Fabric	38.8 m2/hr (F6460) / 24.3 m2/hr (F6460H)
Production Hard Surface	7.0 m2/hr (F6460) / 4.3 m2/hr (F6460H)
MEDIA SUPPORT	
Loading	Single roll, 103 mm max diameter with 2" core or
	150 mm max diameter with 3" core, 0.08-0.5 mm
	thick (75 gsm or greater), 254-1118 mm width,
Min Print Margins	3 mm left/right, 5 mm top/bottom
OPERATION	
Output	Sheet based with integrated auto cutter
	Roll based with optional ⁴ ATU (432~1118 mm wide)
Control Panel	4.3" touchscreen with in-built help & QR-Code support
Utility Software	Epson Edge Dashboard with downloadable print
	profiles, Epson Accounting Tool and Epson Cloud
DID 0-#	Solution PORT (ECSP) with integrated server
RIP Software Interface	Ships with Epson Edge Print PRO (Win only)
	USB 3.0 and Ethernet (recommended) 1 GB
Memory ENVIRONMENTAL	
Operational Temp	10~35°C (15~25°C recommended)
Operational Humidity	20~80% (no condensation, 40~60% recommended)
Power Supply	AC - 240 V, 50 Hz - 60 Hz, 1.6 A
Power Consumption	80 W operating / 36 W standby / 19 W sleep
Operating Noise	53.5 dB
operating Noise	50.5 UD

Weight 120 kg (F6460 no ATU) / 140 kg (F6460H) Shipping Carton F6460 2.1 x 0.9 x 1.2 m, 186 kg Shipping Carton F6460H 2.1 x 1.3 x 1.2 m, 239 kg WHAT'S IN THE BOX³ Printer, stand, power cable, ATU (F6460H only), roll media adaptor set, reusable waste tank, maintenance kit, head cleaning kit, HDkCYM ink set, 1 x roll Epson Transfer Media, utility software, RIP license & user manual. **CONFIGURATION OPTIONS⁴** SCF64601Y 4c Printer with 1 Yr Warranty SCF64603Y 4c Printer with 1 Yr Wty + 2 Yr CoverPlus SCF64605Y 4c Printer with 1 Yr Wty + 4 Yr CoverPlus SCF6460H1Y 6c Printer with 1 Yr Warranty 6c Printer with 1 Yr Wty + 2 Yr CoverPlus SCF6460H3Y SCF6460H5Y 6c Printer with 1 Yr Wty + 4 Yr CoverPlus **OPTIONAL ACCESSORIES** Optional³ auto take-up (ATU) system C12C934671 C12C934701 Additional roll media adapter set CONSUMABLES C13S210063 Maintenance kit C13T724000 Replacement 2L waste tank C13S400145 Head cleaning kit C13S902006 Replacement auto cutter blade C13T53L200/300/400/900 2 x 1.6L C/Y/M/HDk Ink pouches C13T46D500/600 2 x 1.6L Lc/Lm lnk pouches C13T46D700/800 2 x 1.6L Fy/Fp Ink pouches C13T46DA00/D00 2 x 1.6L Or/Vi Ink pouches

1608 x 745 (916 with ATU) x 1128 mm

The Epson dye sublimation ink used in the SureColor F6460 & F6460H printers when applied to polyester fabric, pass the requirements of the Oeko-Tex Standard 100 for human ecological requirements of Class I products for adults, children, and babies up to 36 months. The standard specifies testing criteria for the presence of harmful substances within a textile product and belongs to the International Association for Research and Testing in the field of Textile Ecology (Oeko-Tex).

- Volucit and belongs to the international Association for Research and result in the lead of retuite Coology (Ceko-Tex). Warranty is provided for all non-consumable items associated with printers sourced through Epson Australia. Cover includes print heads. It can be extended through the purchase of optional CoverPlus, either separately or as part of a configuration package. Free on-site repair is provided in major metro locations. Service is conditional on a range of factors including appropriate product usage, operation within the printer duty cycle, regular and appropriate user maintenance, use of correct and Genuine Epson consumables, activation and connection to the Epson Cloud Solution PORT system. Please see the Epson Australia and New Zealand web sites for full terms and conditions.
- Performance figures are printer speeds only; actual production times will vary depending on computing platform, print application, file format, size and networking configuration.
 ATU is optional with the F6460 and included with the F6460H.
- Additional Lc/Lm or Fy/Fp or Or/Vi ink must be ordered separately with the F6460H. The independent sourcing and use of a heat press will be required and an external heater/blower unit is generally recommended for ATU operation.



Cost-effective mess-free 1.6L ink pouches load via a tray system



OEKO-TEX®

ECO PASSPORT

Easy operation and maintenance with QR-code video guidance

Optional³ ATU for efficient roll-to-roll production with a calendar style heat press





Supplied with RIP software & backed by advanced support enabled by ECS PORT



Better Products for a Better Future

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. All print samples shown herein are simulations. Specifications are subject to change without notice; customers should review material posted on the web sites listed below for the latest information. V2.0 Nov. 2022

EPSON AUSTRALIA Level 1, 3 Talavera Rd Macquarie Park NSW 2113 Tel: (02) 8899 3666 www.epson.com.au ABN 91 002 625 783

EPSON NEW ZEALAND Level 2, 7-9 Fanshawe Street Auckland 1010 Tel: (09) 366 6855 www.epson.co.nz