

PROJECTOR RANGE GUIDE



**TRUE
COLOURS**
Brighter, vivid projection from Epson



EPSON

	ENTRY BUSINESS				
Note: Highlighted boxes indicate step-ups between models / within series					
	EB-W55	EB-FH54	EB-972	EB-982W	EB-994F
Product Code	V11HB58053	V11HB59053	V11H986053	V11H987053	V11HB60053
IMAGE					
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp
Resolution	WXGA	1080p	XGA	WXGA	1080p
Colour Light Output	4,000 lm	4,100 lm	4,100 lm	4,200 lm	4,100 lm
White Light Output	4,000 lm	4,100 lm	4,100 lm	4,200 lm	4,100 lm
Native Aspect Ratio	16:10	16:9	4:3	16:10	16:9
Contrast Ratio	16,000:1	16,000:1	16,000:1	16,000:1	16,000:1
Lamp Type	210 W UHE	230 W UHE	230 W UHE	230 W UHE	230 W UHE
Keystone Correction (Standard Lens)	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°
OPTICAL (for Standard Lens)					
Zoom	1 – 1.2 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)
Screen Size	33" to 320"	31" to 304"	27" to 262"	29" to 280"	31" to 304"
Projection Distance	60" screen (1.68 – 2.02 m)	60" screen (1.73 – 2.80 m)	60" screen (1.93 – 3.14 m)	60" screen (1.79 – 2.92 m)	60" screen (1.73 – 2.80 m)
Throw Ratio	1.30 (Zoom: Wide) 1.56 (Zoom: Tele)	1.30 (Zoom: Wide) 2.09 (Zoom: Tele)	1.58 (Zoom: Wide) 2.56 (Zoom: Tele)	1.38 (Zoom: Wide) 2.24 (Zoom: Tele)	1.30 (Zoom: Wide) 2.09 (Zoom: Tele)
Focus Method	Manual	Manual	Manual	Manual	Manual
CONNECTIVITY					
Input: Video	-	-	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)
Input: Computer	1 x USB 2.0 type A, 1 x USB 2.0 type B	1 x USB 2.0 type A, 1 x USB 2.0 type B	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type A, 1 x USB 2.0 type B
Input: Digital	2 x HDMI	2 x HDMI	2 x HDMI	2 x HDMI	2 x HDMI
Input: Audio	-	-	1 x RCA (Red / White), 2 x Stereo mini	1 x RCA (Red / White), 2 x Stereo mini	1 x RCA (Red / White), 2 x Stereo mini, 1 x Stereo mini (mic)
Control: I / O	-	-	1 x RS232C	1 x RS232C	1 x RS232C
Network: I / O	-	-	1 x RJ45, 1 x USB 2.0 type A (for Optional Wireless LAN)	1 x RJ45, 1 x USB 2.0 type A (for Optional Wireless LAN)	1 x RJ45
Wireless Connectivity	Included	Included	Optional (ELPAP11)	Optional (ELPAP11)	Included
Output: Video	-	-	1 x D-sub 15-pin	1 x D-sub 15-pin	1 x D-sub 15-pin
Output: Audio	-	1x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES					
Built-in Speaker	2 W	16 W	16 W	16 W	16 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
AirPlay	-	Yes	-	-	Yes
Miracast	-	Yes	-	-	Yes
Split Screen	Yes	-	Yes	Yes	Yes
Auto Keystone Correction	Vertical: ±30°	Vertical: ±30°	Vertical: ±30°	Vertical: ±30°	Vertical: ±30°
Horizontal Slide Keystone Correction	Yes	Yes	Yes	Yes	Yes
Instant Off	Yes	Yes	Yes	Yes	Yes
Direct Power On	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, password protect function				
Colour Modes	Dynamic, Presentation, Cinema, sRGB, Blackboard				
GENERAL					
Dimensions D x W x H (Including feet)	234 x 302 x 87 mm	282 x 309 x 90 mm	293 x 309 x 105 mm	293 x 309 x 105 mm	282 x 309 x 90 mm
Weight	2.6 kg	3.1 kg	3.1 kg	3.1 kg	3.1 kg
Lamp Life (Normal / Eco)	6,000 h / 12,000 h	5,500 h / 12,000 h	6,500 h / 17,000 h	6,500 h / 17,000 h	6,500 h / 17,000 h
Power Consumption: Lamp On	332 W	332 W	327 W	327 W	332 W
Power Consumption: Standby	2.0 W	-	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	37 / 28 dB	37 / 28 dB	37 / 28 dB	37 / 28 dB	37 / 28 dB

	PORTABLE BUSINESS		MID-RANGE BUSINESS		
					
	EB-1780W	EB-1795F	EB-L260F	EB-2250U	EB-2265U
Product Code	V11H795053	V11H796053	V11HA69053	V11H871053	V11H814053
IMAGE					
Light Source	Lamp	Lamp	Laser Diode	Lamp	Lamp
Resolution	WXGA	1080p	1080p	WUXGA	WUXGA
Colour Light Output	3,000 lm	3,200 lm	4,600 lm	5,000 lm	5,500 lm
White Light Output	3,000 lm	3,200 lm	4,600 lm	5,000 lm	5,500 lm
Native Aspect Ratio	16:10	16:9	16:9	16:10	16:10
Contrast Ratio	10,000:1	10,000:1	2,500,000:1	15,000:1	15,000:1
Lamp Type	206 W UHE	214 W UHE	Laser	300 W UHE	300 W UHE
Keystone Correction (Standard Lens)	Vertical: $\pm 45^\circ$ / Horizontal: $\pm 30^\circ$	Vertical: $\pm 45^\circ$ / Horizontal: $\pm 30^\circ$	Vertical: $\pm 30^\circ$ / Horizontal: $\pm 30^\circ$	Vertical: $\pm 30^\circ$ / Horizontal: $\pm 30^\circ$	Vertical: $\pm 30^\circ$ / Horizontal: $\pm 30^\circ$
OPTICAL (for Standard Lens)					
Zoom	1 – 1.2 (Optical)	1 – 1.2 (Optical)	1 – 1.62 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)
Screen Size	30" to 300"	30" to 300"	31" to 310"	50" to 300"	50" to 300"
Projection Distance	60" screen (1.35 – 1.62 m)	60" screen (1.35 – 1.64 m)	62" screen (1.8 m)	80" screen (2.36 – 3.92 m)	80" screen (2.36 – 3.92 m)
Throw Ratio	1.04 (Zoom: Wide) 1.26 (Zoom: Tele)	1.02 (Zoom: Wide) 1.23 (Zoom: Tele)	1.32 (Zoom: Wide) 2.12 (Zoom: Tele)	1.38 (Zoom: Wide) 2.28 (Zoom: Tele)	1.38 (Zoom: Wide) 2.28 (Zoom: Tele)
Focus Method	Manual	Powered	Manual	Manual	Manual
CONNECTIVITY					
Input: Video	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)
Input: Computer	1 x D-sub 15-pin (RGB), 1 x USB 2.0 type B		2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B		
Input: Digital	1 x HDMI (1 x MHL)	1 x HDMI (1 x MHL)	2 x HDMI	2 x HDMI (1 x MHL)	2 x HDMI (1 x MHL), 1 x HDBaseT
Input: Audio	1 x Stereo mini	1 x Stereo mini	1 x RCA (Red / White), 2 x Stereo mini		
Control: I / O	1 x USB 2.0 type B	1 x USB 2.0 type B	1 x USB 2.0 type B, 1 x RS232C		
Network: I / O	1 x USB 2.0 type A	1 x USB 2.0 type A	1 x RJ45, 1 x USB 2.0 type A	1 x RJ45, 1 x USB 2.0 type A (for Optional Wireless LAN)	1 x RJ45, 1 x USB 2.0 type A
HDBaseT	-	-	-	-	Yes
Wireless Connectivity	Included	Included	Included	Optional (ELPAP10)	Included
Output: Video	-	-	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)
Output: Audio	-	-	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES					
Built-in Speaker	1 W	1 W	16 W	16 W	16 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
Miracast	-	Yes	Yes	Yes	Yes
Split Screen	Yes	Yes	Yes	Yes	Yes
Auto Keystone Correction	Vertical: $\pm 30^\circ$	Vertical: $\pm 30^\circ$	Vertical: $\pm 30^\circ$ / Horizontal: $\pm 30^\circ$	Vertical: $\pm 30^\circ$ / Horizontal: $\pm 20^\circ$	Vertical: $\pm 30^\circ$ / Horizontal: $\pm 20^\circ$
Gesture Presenter	-	Yes	-	Yes	Yes
NFC (Near Field Communication)	-	Yes	-	-	-
Screen Fit	-	Yes	-	Yes	Yes
Instant Off	Yes	Yes	Yes	Yes	Yes
Direct Power On	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, password protect function		Padlock & security cable hole, Kensington® – style lock provision, Wireless LAN unit lock, password protect function		
Colour Modes	Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM		Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM, Multi-Projection	Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM	
GENERAL					
Dimensions D x W x H (Including feet)	213 x 292 x 53 mm	213 x 292 x 53 mm	299 x 325 x 105 mm	291 x 377 x 110 mm	291 x 377 x 110 mm
Weight	1.8 kg	1.8 kg	4.2 kg	4.8 kg	4.9 kg
Light Source Life (Normal / Eco)	4,000 h / 7,000 h	4,000 h / 7,000 h	20,000 h / 30,000 h	5,000 h / 10,000 h	5,000 h / 10,000 h
Power Consumption: Lamp On	277 W	295 W	272 W	420 W	450 W
Power Consumption: Standby	2.0 W	2.0 W	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	39 / 30 dB	39 / 30 dB	36 / 27 dB	39 / 29 dB	39 / 29 dB

Note: Highlighted boxes indicate step-ups between models / within series	SHORT-THROW		ULTRA-SHORT THROW		
					
	EB-L210SF	EB-685W	EB-770F	EB-805F	EB-810E
Product Code	V11HA75053	V11H744553	V11HA79053	V11H923653	V11HA99053
IMAGE					
Light Source	Laser Diode	Lamp	Laser Diode	Laser Diode	Laser Diode
Resolution	1080p	WXGA	1080p	Full HD*	1080p
Colour Light Output	4,000 lm	3,500 lm	4,100 lm	5,000 lm	5,000 lm
White Light Output	4,000 lm	3,500 lm	4,100 lm	5,000 lm	5,000 lm
Native Aspect Ratio	16:9	16:10	16:9	16:9 up to 130"	16:9
Contrast Ratio	2,500,000:1	14,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Lamp Type	Laser	250 W UHE	Laser	Laser	Laser
Keystone Correction (Standard Lens)	Vertical: ±15° Horizontal: ±15°	Vertical: ±3° Horizontal: ±3°	Vertical: ±3° Horizontal: ±3°	Vertical: ±3° Horizontal: ±3°	-
OPTICAL (for Standard Lens)					
Zoom	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)
Screen Size	55" to 125"	60" to 100"	60" to 150" @ 16:9 57" to 142" @ 21:9	65" to 130" @ 16:9 61" to 120" @ 16:6	60" to 160" @ 16:9 57" to 150" @ 21:9
Projection Distance	90" screen (0.91 m)	74.3" screen (0.44 m)	77.0" screen (0.43 m)	96" screen (0.80 m)	90" screen (0.32 m)
Throw Ratio	0.45 (Zoom: Wide) 0.61 (Zoom: Tele)	0.28 (Zoom: Wide) 0.37 (Zoom: Tele)	0.25 (Zoom: Wide) 0.35 (Zoom: Tele)	0.27 (Zoom: Wide) 0.37 (Zoom: Tele)	0.16 (Zoom: Wide) 0.22 (Zoom: Tele)
Focus Method	Manual	Manual	Manual	Manual	Manual
CONNECTIVITY					
Input: Video	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	-
Input: Computer	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B				1 x USB 2.0 type B
Input: Digital	2 x HDMI	3 x HDMI (1 x MHL)	3 x HDMI	3 x HDMI	2 x HDMI
Input: Audio	1 x RCA (Red / White), 2 x Stereo mini, 1 x Mic-in Stereo mini	3 x Stereo mini, 1 x Mic-in Stereo mini		3 x Stereo mini	-
Control: I / O	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin
Network: I / O	1 x RJ45, 1 x USB type A (for Optional Wireless LAN)			1 x RJ45, 2 x USB type A (for Optional Wireless LAN)	
HDBaseT	-	-	-	Yes	Yes
Wireless Connectivity	Included	Optional (ELPAP10)	Included	Optional (ELPAP10)	Included
Output: Video	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB), 1 x HDMI	1 x HDMI
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	-
ADVANCED FEATURES					
Built-in Speaker	16 W	16 W	16 W	16 W	16 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
4K Enhancement	-	-	-	-	Yes
Split Screen	Yes	Yes	Yes	Yes	Yes
Content Playback	Yes	Yes	Yes	Yes	Yes
High Dynamic Range	-	-	-	-	Yes
Scene Adaptive Gamma	Yes	-	Yes	-	Yes
Edgeblending	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, padlock & security cable hole, Wireless LAN unit lock, password protect function				
Colour Modes	Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM, Multi-Projection				Dynamic, Presentation, Cinema, Natural, BlackBoard, DICOM SIM, Multi-Projection, Face brightness
GENERAL					
Dimensions D x W x H (Including Feet)	337 x 325 x 131 mm	400 x 367 x 187 mm	395 x 357 x 165 mm	450 x 458 x 227.5 mm	341 x 695 x 156 mm
Weight	4.6 kg	5.7 kg	5.9 kg	9.4 kg	12.5 kg
Light Source Life (Normal / Eco)	20,000 h / 30,000 h	5,000 h / 10,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h
Power Consumption: Lamp / LD On	260 W	354 W	263 W	366 W	380 W
Power Consumption: Standby	2.0 W	2.3 W	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	37 / 27 dB	35 / 30 dB	37 / 27 dB	36 / 27 dB	35 / 26 dB
Projector Wall Mount	Optional (ELPMB64)	Optional (ELPMB62)	Optional (ELPMB62)	Optional (ELPMB62)	Optional (ELPMB75)

*PIXEL SHIFTING TECHNOLOGY ACHIEVES FULL HD RESOLUTION ON SCREEN

INTERACTIVE ULTRA-SHORT THROW

Note: Highlighted boxes indicate step-ups between models / within series



EB-760Wi



EB-770Fi



EB-1480Fi



EB-1485Fi

Product Code	V11HA80053	V11HA78053	V11H921553	V11H919053
--------------	------------	------------	------------	------------

IMAGE

Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WXGA	1080p	Full HD*	Full HD*
Colour Light Output	4,100 lm	4,100 lm	5,000 lm	5,000 lm
White Light Output	4,100 lm	4,100 lm	5,000 lm	5,000 lm
Native Aspect Ratio	16:10	16:9	16:9 up to 100"	16:9 up to 100" 16:6 up to 120"
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Keystone Correction (Standard Lens)	Vertical: ±3° / Horizontal: ±3°			

OPTICAL (for Standard Lens)

Zoom	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)
Screen Size	58" to 146" @ 16:9 60" to 150" @ 16:10	60" to 150" @ 16:9 57" to 142" @ 21:9	65" to 100" @ 16:9	65" to 100" @ 16:9 61" to 120" @ 16:6
Projection Distance	74.3" screen (0.43 m)	76" screen (0.43 m)	80" screen (0.49 m)	80" screen (0.49 m)
Throw Ratio	0.27 (Zoom: Wide) 0.37 (Zoom: Tele)	0.25 (Zoom: Wide) 0.35 (Zoom: Tele)	0.27 (Zoom: Wide) / 0.37 (Zoom: Tele)	
Focus Method	Manual	Manual	Manual	Manual

CONNECTIVITY

Input: Video	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)
Input: Computer	2 x RGB D-sub 15-pin, 2 x USB 2.0 type B			
Input: Digital	3 x HDMI	3 x HDMI	3 x HDMI	3 x HDMI, 1 x HDBaseT
Input: Audio	3 x Stereo mini, 1 x Mic-In Stereo mini			
Control: I / O	1 x RS-232C D-sub 9-pin, Interactive sync stereo mini - 1 x in / 1 x out, Touch Unit control - 1 x mini DIN 8-pin			
Network: I / O	1 x RJ45, 2 x USB type A (for Optional Wireless LAN)		1 x RJ45, 1 x USB type A (for Optional Wireless LAN)	
Touch Interactive	Mini DIN 8-pin	Mini DIN 8-pin	Mini DIN 8-pin	Mini DIN 8-pin
HDBaseT	-	-	-	Yes
Wireless Connectivity	Included	Included	Included	Included
Output: Video	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB), 1 x HDMI	1 x D-sub 15-pin (RGB), 1 x HDMI
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini

ADVANCED FEATURES

Built-in Speaker	16 W	16 W	2 x 8 W	2 x 8 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes
Interactivity	Pen Included, Finger Optional	Pen Included, Finger Optional	Pen Included, Finger Optional	Pen and Finger Included
Auto Screen Set Up	Yes	Yes	Yes	Yes
Miracast	Yes	Yes	Yes	Yes
Finger Touch Unit (FTU)	Optional (ELPFT01)			Included
Split Screen	Yes	Yes	Yes	Yes
Edge Blending	-	Yes	-	Yes
Scene Adaptive Gamma	Yes	Yes	-	-
Whiteboard Functioning	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes
FTU Mount	Optional (ELPMB63)			
Direct Power On / Off	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, padlock & security cable hole, Wireless LAN unit lock, password protect function			

GENERAL

Dimensions D x W x H (Including Feet)	395 x 357 x 165 mm	395 x 357 x 165 mm	450 x 458 x 223.5 mm	450 x 458 x 223.5 mm
Weight	6 kg	6 kg	9.7 kg	9.7 kg
Light Source Life (Normal / Eco)	20,000 h / 30,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h
Power Consumption: LD On	263 W	263 W	366 W	366 W
Power Consumption: Standby	2.0 W	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	37 / 27 dB	37 / 27 dB	36 / 27 dB	36 / 27 dB
Projector Wall Mount	Optional (ELPMB62)			Included (ELPMB62)

*PIXEL SHIFTING TECHNOLOGY ACHIEVES FULL HD RESOLUTION ON SCREEN

LARGE VENUE

Note: Highlighted boxes indicate step-ups between models / within series



EB-L690U



EB-L790U



EB-L890U



EB-L895U

Product Code	V11HB29053BU	V11HB28053BU	V11HB27053BU	V11HB27153BU
--------------	--------------	--------------	--------------	--------------

IMAGE

Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WUXGA	WUXGA	WUXGA	WUXGA
Colour Light Output	6,500 lm	7,300 lm	8,000 lm	8,000 lm
White Light Output	6,500 lm	7,300 lm	8,000 lm	8,000 lm
Native Aspect Ratio	16:10	16:10	16:10	16:10
Contrast Ratio	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
LD Input Power	244 W	270 W	322 W	322 W
Keystone Correction (Standard Lens)	Vertical: ±30° / Horizontal: ±30°			
Lens Shift (Standard Lens)	Vertical: ±50% / Horizontal: ±20%			

OPTICAL (for Standard Lens)

Zoom	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)
Screen Size	50" to 500"	50" to 500"	50" to 500"	50" to 500"
Projection Distance	80" screen (2.33 – 3.78 m)			
Throw Ratio	1.35 (Zoom: Wide) / 2.20 (Zoom: Tele)			
Focus Method	Manual	Manual	Manual	Manual

CONNECTIVITY

Input: Computer	2 x USB type A (for PC free, document camera) / 1 x USB type B (firmware update)			
Input: Digital	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT
Input Control: I / O	1 x RS-232C	1 x RS-232C	1 x RS-232C	1 x RS-232C
Network I / O	1 x RJ45			
HDBaseT	Yes	Yes	Yes	Yes
Wireless Connectivity	Built-in	Built-in	Built-in	Built-in
Output: Digital	1 x HDMI	1 x HDMI	1 x HDMI	1 x HDMI
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini

ADVANCED FEATURES

Built-in Speaker	10 W	10 W	10 W	10 W
NFC	Yes	Yes	Yes	Yes
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes
Epson Projector Professional Tool	Yes	Yes	Yes	Yes
Epson Projector Content Manager	Yes	Yes	Yes	Yes
Wireless LAN Enterprise Security	Yes	Yes	Yes	Yes
Miracast	Yes	Yes	Yes	Yes
Split Screen	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes
Scene Adaptive Gamma	Yes	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes	Yes
Content Playback	Yes	Yes	Yes	Yes

Security	Kensington® – style lock provision, Wireless LAN Unit Lock, Padlock & security cable hole			
----------	---	--	--	--

GENERAL

Dimensions D x W x H (Including Feet)	340 x 440 x 138 mm			
Weight	8.2 kg	8.2 kg	8.5 kg	8.5 kg
Power Consumption: LD On	399 W	399 W	450 W	450 W
Power Consumption: Standby	2.4 W	2.4 W	2.4 W	2.4 W
Noise Level (Normal/Eco)	32 / 25 dB	34 / 25 dB	36 / 26 dB	36 / 26 dB

LARGE VENUE

Note: Highlighted boxes indicate step-ups between models / within series



EB-L690SE



EB-L790SU



EB-L795SE



EB-L890E

Product Code	V11HB36053BU	V11HB30053BU	V11HB26153BU	V11HB24053BU
--------------	--------------	--------------	--------------	--------------

IMAGE

Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WUXGA (4KE)	WUXGA	WUXGA (4KE)	WUXGA (4KE)
Colour Light Output	6,000 lm	7,000 lm	7,000 lm	8,000 lm
White Light Output	6,000 lm	7,000 lm	7,000 lm	8,000 lm
Native Aspect Ratio	16:10	16:10	16:10	16:10
Contrast Ratio	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
LD Input Power	292 W	322 W	322 W	322 W
Keystone Correction (Standard Lens)	Vertical: ±30° / Horizontal: ±30°			
Lens Shift (Standard Lens)	Vertical: ±50% / Horizontal: ±20%			

OPTICAL (for Standard Lens)

Zoom	1 – 1.4 (Optical)	1 – 1.7 (Optical)	1 – 1.7 (Optical)	1 – 1.6 (Optical)
Screen Size	100" to 500"	60" to 400"	60" to 400"	50" to 500"
Projection Distance	100" screen (1.08 – 1.54 m)	80" screen (1.37 – 2.34 m)	80" screen (1.37 – 2.34 m)	80" screen (2.39 – 3.90 m)
Throw Ratio	0.50 (Zoom: Wide) / 0.07 (Zoom: Tele)	0.79 (Zoom: Wide) / 1.36 (Zoom: Tele)	0.79 (Zoom: Wide) / 1.36 (Zoom: Tele)	1.35 (Zoom : Wide) / 2.20 (Zoom : Tele)
Focus Method	Manual	Manual	Manual	Manual

CONNECTIVITY

Input: Computer	2 x USB type A (for PC free, document camera) / 1 x USB type B (firmware update)			
Input: Digital	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT
Input Control: I / O	1 x RS-232C	1 x RS-232C	1 x RS-232C	1 x RS-232C
Network I / O	1 x RJ45			
HDBaseT	Yes	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11*)	Built-in	Built-in	Built-in
Output: Digital	1 x HDMI	1 x HDMI	1 x HDMI	1 x HDMI
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini

ADVANCED FEATURES

Built-in Speaker	-	10 W	10 W	10 W
4K Enhancement	Yes	-	Yes	Yes
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes
Epson Projector Professional Tool	Yes	Yes	Yes	Yes
Epson Projector Content Manager	Yes	Yes	Yes	Yes
AirPlay	-	Yes	Yes	Yes
Miracast	-	Yes	Yes	Yes
Split Screen	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes
Scene Adaptive Gamma	Yes	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes	Yes
Content Playback	Yes	Yes	Yes	Yes

Security Kensington® – style lock provision, Wireless LAN Unit Lock, Padlock & security cable hole

GENERAL

Dimensions D x W x H (Including Feet)	368 x 440 x 151 mm	362 x 440 x 151 mm	362 x 440 x 151 mm	340 x 440 x 138 mm
Weight	9.3 kg	9.2 kg	9.3 kg	8.5 kg
Power Consumption: LD On	415 W	450 W	450 W	450 W
Power Consumption: Standby	2.4 W	2.4 W	2.4 W	2.4 W
Noise Level (Normal/Eco)	36 / 26 dB			

*WI-FI CONNECTIVITY AVAILABLE ONLY WITH ELPAP11.

LARGE VENUE*

Note: Highlighted boxes indicate step-ups between models / within series



EB-PU1007WNL



EB-PU1008WNL



EB-PU1008BNL



EB-PU2010WNL



EB-PU2010BNL

Product Code	V11HA34953BU	V11HA33953BU	V11HA33853BU	V11HA52953BU	V11HA52853BU
--------------	--------------	--------------	--------------	--------------	--------------

IMAGE

Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA
Colour Light Output	7,000 lm	8,500 lm	8,500 lm	10,000 lm	10,000 lm
White Light Output	7,000 lm	8,500 lm	8,500 lm	10,000 lm	10,000 lm
Native Aspect Ratio	16:10	16:10	16:10	16:10	16:10
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
LD Input Power	291 W	372 W	372 W	388 W	388 W
Referenced Standard Lens	ELPLM08	ELPLM08	ELPLM08	ELPLM15	ELPLM15
Keystone Correction (Standard Lens)	Vertical: ±45° / Horizontal: ±30°				
Lens Shift (Standard Lens)	Vertical: ±67% / Horizontal: ±30%			Vertical: ±60% / Horizontal: ±18%	

OPTICAL (for Standard Lens)

Zoom	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)
Screen Size	50" to 1000"	50" to 1000"	50" to 1000"	60" to 1000"	60" to 1000"
Projection Distance	100" screen (3.11 – 5 m)			100" screen (3.38 – 5 m)	
Throw Ratio	1.44 (Zoom: Wide) / 2.32 (Zoom: Tele)			1.57 (Zoom: Wide) / 2.56 (Zoom: Tele)	
Focus Method	Powered	Powered	Powered	Powered	Powered

CONNECTIVITY

Input: Computer	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)
Input: Digital	1 x HDMI, 1 x DVI-D, 1 x HDBaseT			1 x HDMI, 1 x DVI-D, 1 x HDBaseT	
Input: SDI	-	-	-	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Control: I / O	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini
Network: I / O	1 x RJ45, 1 x USB type A (for Optional Wireless LAN)				
HDBaseT	Yes	Yes	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)
Output: Digital	-	-	-	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini

ADVANCED FEATURES

Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
Epson Professional Tool	Yes	Yes	Yes	Yes	Yes
Remote Access Camera	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)
External Air Filter (High capacity)	Optional (ELPAF63)	Optional (ELPAF63)	Optional (ELPAF63)	Optional (ELPAF63)	Optional (ELPAF63)
Wireless LAN Enterprise Security	Yes (with Optional Wireless LAN Unit)				
4K Enhancement	Yes	Yes	Yes	Yes	Yes
Art-Net	Yes	Yes	Yes	Yes	Yes
Lens Position Memory	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)
Split Screen	Yes	Yes	Yes	Yes	Yes
Edge Blending	Yes	Yes	Yes	Yes	Yes
Curved Screen Projection	Yes	Yes	Yes	Yes	Yes
Frame Interpolation	Yes	Yes	Yes	Yes	Yes
Super-resolution	Yes	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, Wireless LAN Unit Lock, Security cable hole				
Colour Modes	Dynamic, Presentation, Cinema, BT.709, Natural, DICOM SIM, Multi-Projection				

GENERAL

Dimensions D x W x H (Including Feet)	436 x 545 x 189 mm				
Weight	16.4 kg	16.4 kg	16.4 kg	17.0 kg	17.0 kg
Power Consumption: LD On	366 W	452 W	452 W	452 W	452 W
Noise Level (Normal/Eco)	34 / 30 dB	36 / 30 dB	36 / 30 dB	37 / 30 dB	37 / 30 dB

LARGE VENUE*

Note: Highlighted boxes indicate step-ups between models / within series



EB-PU2213B

V11HA68853BU



EB-PU2216B

V11HA67853BU



EB-PU2220B

V11HA66853BU



EB-L3000UNL

V11H944853BU

IMAGE

Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WUXGA	WUXGA	WUXGA	WUXGA
Colour Light Output	13,000 lm	16,000 lm	20,000 lm	30,000 lm
White Light Output	13,000 lm	16,000 lm	20,000 lm	30,000 lm
Native Aspect Ratio	16:10	16:10	16:10	16:10
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
LD Input Power	562 W	746 W	934 W	1,670 W
Keystone Correction (Standard Lens)	Vertical: ±45° / Horizontal ±30°			
Lens Shift (Standard Lens)	Vertical: ±60% / Horizontal: ±18%	Vertical: ±60% / Horizontal: ±18%	Vertical: ±60% / Horizontal: ±18%	Vertical: ±65% / Horizontal: ±30%

OPTICAL (for Standard Lens)

Zoom	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.35 (Optical)
Screen Size	60" to 1000"	60" to 1000"	60" to 1000"	100" to 1000"
Projection Distance	100" screen (3.37 – 5.49 m)	100" screen (3.37 m)	100" screen (3.37 m)	200" screen (7.48 – 10.11 m)
Throw Ratio		1.57 (Zoom: Wide) / 2.56 (Zoom: Tele)		1.74 (Zoom: Wide) / 2.35 (Zoom: Tele)
Focus Method	Powered	Powered	Powered	Powered

CONNECTIVITY

Input: Video	-	-	-	1 x 5BNC
Input: Computer	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)
Input: Digital		1 x HDMI, 1 x DVI-D, 1 x HDBaseT		1 x HDMI, 1 x DVI-D, 1 x HDBaseT
Input: SDI	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Control: I / O	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini
Network: I / O	1x RJ45 (Art-Net), 1 x USB type A (for Optional Wireless LAN), 1 x USB type B (service)			
HDBaseT	Yes	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)
Output: Digital	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	-

ADVANCED FEATURES

Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes
Epson Professional Tool	Yes	Yes	Yes	Yes
Remote Access Camera	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes
Wireless LAN Enterprise Security	Yes (with Optional Wireless LAN Unit)			
4K Enhancement	Yes	Yes	Yes	Yes
Fully Sealed Optical Engine	Yes	Yes	Yes	Yes
Art-Net	Yes	Yes	Yes	Yes
Lens Position Memory	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)
Split Screen	Yes	Yes	Yes	Yes
Edge Blending	Yes	Yes	Yes	Yes
Scaling	Yes	Yes	Yes	Yes
Curved Screen Projection	Yes	Yes	Yes	Yes
Simple Stacking	Yes	Yes	Yes	Yes
NFC	Yes	Yes	Yes	-
Gamma Correction	Yes	Yes	Yes	Yes
Frame Interpolation	Yes	Yes	Yes	Yes
Super-resolution	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes	Yes
Instant Off	Yes	Yes	Yes	Yes

* PLEASE VISIT WWW.EPSON.COM.AU FOR DIMENSIONS AND WEIGHT OF ABOVE MODELS

LARGE VENUE*

Note: Highlighted boxes indicate step-ups between models / within series



EB-PQ2010B



EB-PQ2216B



EB-PQ2220B

Product Code	V11HB02853BU	V11HB04853BU	V11HB05853BU
--------------	--------------	--------------	--------------

IMAGE

Light Source	Laser Diode	Laser Diode	Laser Diode
Resolution	4K** (3840 x 2160, 8.3 million pixels)	4K** (3840 x 2160, 8.3 million pixels)	4K** (3840 x 2160, 8.3 million pixels)
Colour Light Output	10,000 lm	16,000 lm	20,000 lm
White Light Output	10,000 lm	16,000 lm	20,000 lm
Native Aspect Ratio	16:9		
Contrast Ratio	5,000,000:1		
LD Input Power	449 W	810 W	1080 W
Keystone Correction (Standard Lens)	Vertical: ±45° / Horizontal ±30°		
Lens Shift (Standard Lens)	Vertical: ±58% / Horizontal: ±16%		

OPTICAL (for Standard Lens)

Zoom	1 – 1.61 (Optical)		
Screen Size	60" to 1000"		
Projection Distance	100" screen (3.35 m)		
Throw Ratio	1.52 (Zoom: Wide) / 2.47 (Zoom: Tele)		
Focus Method	Powered		

CONNECTIVITY

Input: Digital	2 x HDMI, 1 x HDBaseT, 1 x BNC (12G-SDI)		
Input: SDI	1 x BNC (12G-SDI)		
Control: I / O	1 x RS232C, 1 x Stereo mini		
Network: I / O	1x RJ45 (Art-Net), 1 x USB type A (for Optional Wireless LAN)		
HDBaseT	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)
Output: Digital	1 x HDMI, 1 x BNC (12G-SDI)		
Output: Audio	1 x Stereo mini		

ADVANCED FEATURES

Epson Projector Management (Network & Control)	Yes	Yes	Yes
Epson Professional Tool	Yes	Yes	Yes
Epson Projector Content Manager	Yes	Yes	Yes
Wireless LAN Enterprise Security	Yes (with Optional Wireless LAN unit)		
Remote Access Camera	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)
Fully Sealed Optical Engine	-	Yes	Yes
Art-Net	Yes	Yes	Yes
Fully Sealed Laser Light Source	-	Yes	Yes
Edge Blending	Yes	Yes	Yes
Scaling	Yes	Yes	Yes
Curved Surface Blending Support	Yes	Yes	Yes
NFC	Yes	Yes	Yes
Simple Stacking	Yes	Yes	Yes
Simple Blending	Yes	Yes	Yes
Scene Adaptive Gamma	Yes	Yes	Yes
Frame Interpolation (4K @ 120 Hz)	Yes	Yes	Yes
Super-resolution	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes
HDR10 (High Dynamic Range)	Yes	Yes	Yes
HLG (Hybrid Log Gamma)	Yes	Yes	Yes
Auto Contrast Enhancement	Yes	Yes	Yes
Auto Signal Backup Function	Yes (HDMI, SDI, HDBaseT)		
Colour Modes	Dynamic, Presentation, Cinema, BT.709, Natural, DICOM SIM, Multi-Projection		

* PLEASE VISIT WWW.EPSON.COM.AU FOR DIMENSIONS AND WEIGHT OF ABOVE MODELS

** 1080P WITH 2-AXIS PIXEL SHIFT TECHNOLOGY. ON SCREEN PIXELS = 8,294,400 DOTS (1,920 X 1,080 X 4).

	LIGHTING		ULTRA-SHORT THROW HOME	
				
	EV-110	EV-115	EH-LS650B	EH-LS800B
Product Code	V11HA22053	V11HA22153	V11HB07153	V11HA90153
IMAGE				
Light Source	Laser Diode	Laser Diode	Laser diode	Laser diode
Resolution	WXGA	WXGA	4K Enhancement* (1920 x 1080 x 2)	4K Enhancement* (1920 x 1080 x 2)
Colour Light Output	2,200 lm	2,200 lm	3,600 lm	4,000 lm
White Light Output	2,200 lm	2,200 lm	3,600 lm	4,000 lm
Native Aspect Ratio	16:10	16:10	16:9	16:9
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Lamp Type	Laser	Laser	Laser	Laser
Keystone Correction (Standard Lens)	Vertical: ±45° Horizontal: ±40°	Vertical: ±45° Horizontal: ±40°	-	-
Lens Shift	-	-	-	-
Colour Processing	10-bit	10-bit	10-bit	10-bit
OPTICAL (for Standard Lens)				
Zoom	Total: 1 – 2.2 (Optical: 1 – 1.58, Digital: 1 – 1.4)		1 – 2.5 (Digital)	1 – 2.5 (Digital)
Screen Size	30" to 150"	30" to 150"	60" to 120"	32" to 150"
Projection Distance	60" screen (1.79 m)	60" screen (1.79 m)	77" screen (0.43 m)	90" screen (0.32 m)
Throw Ratio	1.38 (Zoom: Wide) / 2.19 (Zoom: Tele)		0.25 (Zoom: Wide) / 0.62 (Zoom: Tele)	0.16 (Zoom: Wide) / 0.40 (Zoom: Tele)
Focus Method	Powered	Powered	Manual	Manual
CONNECTIVITY				
Input: Digital	1 x HDMI	1 x HDMI	2 x HDMI (HDCP2.3) (HDMI2 supports eARC)	3 x HDMI (HDCP2.3) (HDMI2 supports ARC)
Input: SD Card	1 x SDHC, up to 32 GB		-	-
USB: I / O	1 x USB type A zoom A (Power Supply)	1 x USB type A zoom A (Power Supply)	3x USB type A (2 x for data, 1 x for 5V/2A power supply), 1 x USB B mini (service only)	3 x USB type A, 1 x USB B mini (service)
Control	1 x USB type A for GPI	1 x USB type A for GPI	-	-
Network: I / O	1 x RJ45	1 x RJ45	-	-
Wireless Connectivity	Included	Included	Included	Included
Output: Audio	1 x Stereo mini	1 x Stereo mini	1x S / PDIF	1 x S / PDIF 1 x Stereo mini
ADVANCED FEATURES				
Epson Projector Management (Network & Control)	Yes	Yes	-	-
Edge Blending	Yes	Yes	-	-
Built-in Speaker	-	-	20 W (2 x 2.1ch Satellite, 1 x Subwoofer)	20 W (2 x 2.1ch Satellite, 1 x Subwoofer)
Super Resolution	-	-	Yes	Yes
High Dynamic Range - HDR10	-	-	Yes	Yes
Hybrid Log Gamma - HLG	-	-	Yes	Yes
4K Enhancement	-	-	Yes	Yes
Frame Interpolation	-	-	Yes	Yes
Smart Media Player	-	-	Yes	Yes
Auto Contrast Enhancement	-	-	Yes	Yes
Scene Adaptive Gamma	-	-	Yes	Yes
Colour Modes	Dynamic, Normal		Dynamic, Vivid, Cinema, Natural	
Security	Password protect function		Kensington – style lock provision	
GENERAL				
Dimensions D x W x H (Including Feet)	Projection unit: 175 x D265 Power supply unit: 110 x 459 x 65 mm (with Cable Cover)		400 x 467 x 153 mm	341 x 695 x 156 mm
Weight	6.9 kg	6.9 kg	7.4 kg	12.3 kg
Power Consumption (Normal)	-	-	254 W	335 W
Power Consumption (Standby)	170 W	170 W	2 W	2 W
Noise Level (Normal/Eco)	34 / 22 dB	34 / 22 dB	29 / 20 dB	32 / 19 dB

*4K RESOLUTION ENHANCEMENT TECHNOLOGY SHIFTS EACH PIXEL TO PRODUCE AN IMAGE ON SCREEN, UP TO THE STATED SPECIFICATION.

ENTRY HOME THEATRE

Note: Highlighted boxes indicate step-ups between models / within series



CO-FH02

V11HA85053



EH-TW850

V11HB61053

IMAGE

Light Source	Lamp	Lamp
Resolution	Full HD	Full HD
Colour Light Output	3000 lumens	3400 lumens
White Light Output	3000 lumens	3400 lumens
Native Aspect Ratio	16:9	16:9
Contrast Ratio	350:1	16000:1
Lamp Type	188 W UHE	210 W UHE
Keystone Correction (Standard Lens)	Vertical: ±30° / Horizontal ±30°	Vertical: ±30° / Horizontal ±30°
Colour Processing	8-bit	8-bit

OPTICAL (for Standard Lens)

Zoom	1–1.35 (Digital)	1-1.2 (Optical)
Screen Size	26" to 391"	31" to 305"
Projection Distance	60" screen (1.58 m)	60" screen (1.35 - 1.64 m)
Throw Ratio	1.19 (Zoom: Wide), 1.61 (Zoom: Tele)	1.00 (Zoom: Wide), 1.21 (Zoom: Tele)
Focus Method	Manual	Manual

CONNECTIVITY

Input: Digital	1 x HDMI	2 x HDMI
USB: I / O	1 x USB type A (Power Supply, Firmware Update, copy OSD settings), 1 x USB type B (firmware update)	1 x USB type A 1 x USB type B (firmware update)
Wireless Connectivity	Included (via SMP)	Built-in
Output: Audio	-	1 x Stereo mini

ADVANCED FEATURES

Built-in Speaker	5 W	2 W
Epson Projector Management (Network & Control)	-	Yes
Epson iProjection (Multi-PC Projection)	-	Yes
Miracast	-	Yes
Airplay	-	Yes
Scene Adaptive Gamma	Yes	Yes
Smart media player	Yes	-
Security	Kensington - style lock provision & padlock	

GENERAL

Dimensions D x W x H (Including Feet)	211 x 320 x 87 mm	249 x 302 x 87 mm
Weight	2.6 kg	2.8 kg
Lamp Life (Normal / Eco)	6,000 h / 12,000 h	6,000 h / 12,000 h
Power Consumption (Normal)	270 W	231 W
Power Consumption (Standby)	-	-
Noise Level (Normal/Eco)	37 / 29 dB	37 / 28 dB

MINI HOME THEATRE

Note: Highlighted boxes indicate step-ups between models / within series



EF-21W



EF-21G



EF-22B

Product Code	V11HB35053	V11HB35353	V11HB38153
--------------	------------	------------	------------

IMAGE

Light Source	Laser diode	Laser diode	Laser diode
Resolution	Full HD	Full HD	Full HD
Colour Light Output	1,000 lm	1,000 lm	1,000 lm
White Light Output	1,000 lm	1,000 lm	1,000 lm
Native Aspect Ratio	16:9	16:9	16:9
Contrast Ratio	5,000,000:1	5,000,000:1	5,000,000:1
Lamp Type	Laser diode	Laser diode	Laser diode
Colour Processing	8-bit	8-bit	8-bit

OPTICAL (for Standard Lens)

Zoom	1.0-1.82 (Digital Zoom)	1.0-1.82 (Digital Zoom)	1.0-1.82 (Digital Zoom)
Screen Size	30" to 150"	30" to 150"	30" to 150"
Projection Distance	60" screen (1.33 m)	60" screen (1.33 m)	60" screen (1.33 m)
Throw Ratio	1.0 (Zoom: Wide), 1.81 (Zoom: Tele)	1.0 (Zoom: Wide), 1.81 (Zoom: Tele)	1.0 (Zoom: Wide), 1.81 (Zoom: Tele)
Focus Method	Auto	Auto	Auto

CONNECTIVITY

Input: Digital	1 x HDMI (ARC)	1 x HDMI (ARC)	1 x HDMI (ARC)
USB: I / O	1 x USB type A 1 x USB type B (firmware update)	1 x USB type A 1 x USB type B (firmware update)	1 x USB type A 1 x USB type B (firmware update)
Wireless Connectivity	Built-in	Built-in	Built-in
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini

ADVANCED FEATURES

Built-in Speaker	2 x 5 W	2 x 5 W	2 x 5 W + passive radiator
Bluetooth	Yes	Yes	Yes
Scene Adaptive Gamma	Yes	Yes	Yes
High Dynamic Range	Yes	Yes	Yes
Auto Shape Correction	Yes	Yes	Yes
Obstacle avoidance	Yes	Yes	Yes
Smart media player (Google TV)	Yes	Yes	Yes
Dolby certification (audio)	Yes	Yes	Yes
Security	Padlock	Padlock	Padlock

GENERAL

Dimensions D x W x H (Including Feet)	191 x 197 x 113 mm	191 x 197 x 113 mm	191 x 236 x 193 mm
Weight	2.3 kg	2.3 kg	3 kg
Power Consumption (Normal)	106 W	106 W	103 W
Power Consumption (Standby)	0.5 W	0.5 W	0.5 W
Noise Level (Normal/Eco)	23 / 19 dB	23 / 19 dB	22 / 18 dB

<p>Note: Highlighted boxes indicate step-ups between models / within series</p>	4K HOME THEATRE				
					
	EH-TW6250	EH-TW7100	EH-TW9400	EH-LS9000B	EH-LS12000B
Product Code	V11HA73053	V11H959053	V11H928053	V11HC13153	V11HA47053
IMAGE					
Light Source	Lamp	Lamp	Lamp	Laser diode	Laser diode
Resolution	4K Enhancement* (1920 x 1080 x 2)	4K Enhancement* (1920 x 1080 x 2)	4K Enhancement* (1920 x 1080 x 2)	4K* (8.3 M pixels on screen)	4K* (8.3 M pixels on screen)
Colour Light Output	2,800 lm	3,000 lm	2,600 lm	2,200 lm	2,700 lm
White Light Output	2,800 lm	3,000 lm	2,600 lm	2,200 lm	2,700 lm
Native Aspect Ratio	16:9	16:9	16:9	16:9	16:9
Contrast Ratio	35,000:1	100,000:1	1,200,000:1	2,500,000:1	2,500,000:1
Lamp Type	200 W UHE	250 W UHE	250 W UHE	Laser diode	Laser diode
Keystone Correction (Standard Lens)	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30°	Vertical: ±30° / Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°
Lens Shift	Vertical: ±60%	Vertical: ±60% Horizontal: ±24%	Vertical: ±96.3% Horizontal: ±47.1%	Vertical: ±96.3% Horizontal: ±24%	Vertical: ±96.3% Horizontal: ±47.1%
Colour Processing	10-bit	10-bit	10-bit	10-bit	10-bit
Advanced Image Processing	-	-	Yes	Yes	Yes (32-bit)
OPTICAL (for Standard Lens)					
Zoom	1 – 1.62 (Optical)	1 – 1.6 (Optical)	1 – 2.1 (Optical)	1 - 2.1 (Optical)	1 – 2.1 (Optical)
Screen Size	40" to 500"	40" to 500"	50" to 300"	50" to 300"	50" to 300"
Projection Distance	80" screen (2.34 – 3.81 m)	100" screen (2.95 – 4.77 m)	100" screen (3 – 6.3 m)	100" screen (3.0 – 6.3 m)	100" screen (3.0 – 6.3 m)
Throw Ratio	1.32 (Zoom: Wide) 2.15 (Zoom: Tele)	1.32 (Zoom: Wide) 2.15 (Zoom: Tele)	1.35 (Zoom: Wide) 2.84 (Zoom: Tele)	1.35 (Zoom: Wide) 2.84 (Zoom: Tele)	1.35 (Zoom: Wide) 2.84 (Zoom: Tele)
Focus Method	Manual	Manual	Powered	Powered	Powered
CONNECTIVITY					
Input: Video	1 x HDMI	2 x HDMI	2x HDMI 1x D-sub 15-pin (RGB)	2 x HDMI (HDCP2.3) (HDMI2 supports eARC/ARC)	2 x HDMI (HDCP2.3) (HDMI2 supports eARC/ARC)
USB: I / O	1 x USB mini B (service)	1 x USB type A (Power Supply, Firmware Update), 1 x USB B mini (service)	2 x USB type A, 1 x USB B mini (service)	2 x USB A, 1 x USB B (firmware update, copy OSD settings)	2 x USB type A (1x Opt. HDMI) / 1 x USB B mini (service)
Control	-	1 x RS232C, 1 x Stereo mini	1 x RS232C	1 x RS232c	1 x RS232C
Network: I / O	-	1 x USB type A (for Optional Wireless LAN)	1 x RJ45, 1 x USB type A (for Optional Wireless LAN)	1 x RJ45	1 x RJ45
Wireless Connectivity	Included (via SMP)	Optional (ELPAP10)	Optional (ELPAP10)	-	-
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES					
Built-in Speaker	10 W	2 x 10 W	-	-	-
Super Resolution	-	-	Yes	Yes (4K compatible)	Yes (4K compatible)
High Dynamic Range	Yes	Yes	Yes (HDR 10)	Yes (HDR 10+)	Yes (HDR 10+)
Hybrid Log Gamma - HLG	-	-	Yes	Yes	Yes
4K Enhancement*	Yes	Yes	Yes	Yes	Yes
Frame Interpolation	Yes	Yes	Yes	Yes (up to 4K, 60 FPS)	Yes (up to 4K 60 FPS)
Smart media player	Yes	-	-	Optional (ELPAP12)	Optional (ELPAP12)
Auto Contrast Enhancement	-	-	-	Yes	Yes
Scene Adaptive Gamma	Yes	-	-	Yes	Yes
Direct Power On	Yes	Yes	Yes	Yes	Yes
Scene Adaptive Gamma	Yes	Yes	-	Yes	Yes
Security	Kensington - style lock provision & padlock		Kensington - style lock provision		
Colour Modes	Dynamic, Vivid, Natural, Cinema	Dynamic, Bright Cinema, Natural, Cinema	2D: Dynamic, Bright Cinema, Natural Cinema, Digital Cinema 3D: 3D Dynamic, 3D Cinema	Dynamic, Bright Cinema, Cinema, Natural, Vivid	Dynamic, Bright Cinema, Cinema, Natural, Vivid
GENERAL					
Dimensions D x W x H (Including Feet)	275 x 333 x 131 mm	330 x 410 x 164 mm	450 x 520 x 192.7 mm	447 x 520 x 193 mm	447 x 520 x 192.7 mm
Weight	4.1 kg	6.9 kg	11.2 kg	12.7 kg	12.7 kg
Power Consumption (Normal)	301 W	406 W	298 W	302 W	302 W
Power Consumption (Standby)	-	2 W	2 W	2 W	2 W
Noise Level (Normal/Eco)	36 / 28 dB	35 / 24 dB	31 / 20 dB	30 / 22 dB	30 / 22 dB

*4K RESOLUTION ENHANCEMENT TECHNOLOGY SHIFTS EACH PIXEL TO PRODUCE AN IMAGE ON SCREEN, UP TO THE STATED SPECIFICATION.

PREMIUM HOME THEATRE

Note: Highlighted boxes indicate step-ups between models / within series



EH-QL3000W

V11HB34953



EH-QL3000B

V11HB34853

Product Code

IMAGE

Light Source	Laser diode
Resolution	4K* (3840 x 2160) (8.3 M pixels on screen)
Colour Light Output	6,000 lumens
White Light Output	6,000 lumens
Native Aspect Ratio	16:9
Contrast Ratio	5,000,000:1
Keystone Correction (Standard Lens)	Vertical: ±45% / Horizontal: ±30%
Colour Processing	10-bit

OPTICAL (for Standard Lens)

Zoom	1 – 1.61 (Optical)
Screen Size	60" to 1000"
Projection Distance	100" screen (3.35 m)
Throw Ratio	1.52 (Zoom: Wide), 2.47 (Zoom: Tele)
Focus Method	Powered

CONNECTIVITY

Input: Digital	2 x HDMI (HDCP 2.3)
USB: I / O	2 x USB A (for ELPAP12, firmware update, copy OSD settings, or 5V/2A power supply, content playback)
Control	1 x RS232c
Network: I / O	1 x RJ45
Output: Audio	1 x Stereo mini

ADVANCED FEATURES

Content Playback	Yes
Dynamic Tone Mapping	Yes
4K Enhancement*	Yes
High Dynamic Range – HDR10	Yes
Hybrid Log Gamma – HLG	Yes
Advanced Image Processing	Yes
Super Resolution	Yes (4K compatible)
Frame Interpolation	Yes (up to 4K 60 fps)
Auto Contrast Enhancement	Yes
Scene Adaptive Gamma	Yes
ALLM support (Auto Low Latency Mode)	Yes (4K at 120 fps)
AV Mute	Yes
Direct Power On	Yes
Security	Kensington - style lock provision, lens lock
Colour Modes	Dynamic, Vivid, Cinema, Natural
Lens Position Memory	10 positions
Industry / Partner Standard	Crestron Connected V2, Crestron Integrated Partner, Control4, AMX, PJLink

GENERAL

Dimensions D x W x H (Including Feet)	568 x 568 x 192 mm
Weight	21 kg
Power Consumption (Normal)	437 W
Power Consumption (Standby)	2 W
Noise Level (Normal)	28 dB


*4K RESOLUTION ENHANCEMENT TECHNOLOGY SHIFTS EACH PIXEL TO PRODUCE AN IMAGE ON SCREEN, UP TO THE STATED SPECIFICATION.

OPTIONAL LENSES

EB-L30000U								
Lens type	Rear Projection	Wide Zoom	Wide Zoom	Mid-Throw	Mid-Throw	Mid-Throw	Long-Throw	Long-Throw
Reference	ELPLR05	ELPLU05	ELPLW07	ELPLM12	ELPLM13	ELPLM14	ELPLL09	ELPLL10
Order Number	V12H004X0A	V12H004X0B	V12H004W07	V12H004M0D	V12H004M0E	V12H004L09	V12H004R05	V12H004R05
Throw Ratio	0.63	0.90 – 1.09	1.29 – 1.76	1.74 – 2.35	2.28 – 3.46	3.41 – 5.11	4.79 – 7.20	6.73 – 10.45

EB-PU/PQ Series												
Lens type	Ultra-Short-Throw	Ultra-Short-Throw	Short-Throw	Short-Throw	Wide-Throw	Wide-Throw	Wide-Throw	Mid-Throw	Mid-Throw	Mid-Throw	Mid-Throw	Long-Throw
Reference	ELPLX01S	ELPLX02S	ELPLU03S	ELPLU04	ELPLW05	ELPLW06	ELPLW08	ELPLM08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Order Number	V12H004X01	V12H004X02	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004W08	V12H004M08	V12H004M08	V12H004M0A	V12H004M0B	V12H004L08
Throw Ratio	0.35:1	-	0.65 – 0.78:1	0.87 – 1.06:1	1.04 – 1.46:1	1.63 – 2.22:1	1.18 – 1.66:1	1.45 – 2.32:1	2.15 – 3.49:1	3.31 – 5.07:1	4.48 – 7.39:1	7.2 – 10.12:1
PU2213B / PU2216B / PU2220B	-	0.35:1	0.48 – 0.57:1	0.64 – 0.78:1	0.77 – 1.07:1	1.19 – 1.63:1	0.86 – 1.21:1	1.08 – 1.72:1	1.58 – 2.56:1	2.43 – 3.71:1	3.54 – 5.41:1	5.27 – 7.41:1

OPTIONS AND ACCESSORIES



Air Filters

Regularly replace the air filter in your Epson projector in order to maintain image quality and to ensure longevity.



Lamps

Order genuine Epson lamps to ensure that you achieve the best possible image quality and colour reproduction.



Speakers

Enhance the audio experience with the Epson ELP-SP02 powered speaker set.



Control Pad

A simple cable management solution from Epson. Ideal for classrooms and meeting spaces.



Streaming Media Player

Stream your favourite content with the ELPAP12.



Portable Screen

Epson portable, light weight 120 inch screen is the perfect display solution for your home or office.



Ceiling Mounts

Ceiling mounts to suit all models of Epson projectors.



Wireless LAN Adapter

A simple yet powerful solution to enabling wireless connectivity to your Epson projector (optional models only).

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.