



Workforce 525

Print | Copy | Scan | Fax | Wi-Fi

Engineered
for Business.



Features and Benefits

- Fast print speeds up to 38ppm
- 5 Individual Ink Cartridges (Dual Black inks) – only replace the colour you use
- Choice of ink cartridge capacities available
- Epson DURABrite® Ultra Resin Coated Pigment Ink for water, smudge & fade resistant prints
- Advanced document management with integrated fax & Automatic Document Feeder
- Cable-free printing with 802.11b/g/n Wi-Fi connectivity + 10/100 Ethernet

Printer

| | |
|--------------------------------|---|
| PRINTER TYPE | |
| Epson WorkForce 525 | C11CA78401 |
| PRINTING METHOD | |
| NOZZLE CONFIGURATION | 360 nozzles Black, 59 nozzles each colour (Cyan, Yellow, Magenta) |
| MINIMUM INK DROPLET VOLUME | 3 Picolitres |
| RESOLUTION | |
| | 5760 x 1440 optimised dpi with (with Variable Sized Droplet Technology) 5760 dpi with Variable Sized Droplet Technology |
| PRINT SPEED | |
| BLACK TEXT (MEMO) A4 (DRAFT)^ | Approx. 38ppm* |
| COLOUR TEXT (MEMO) A4 (DRAFT)^ | Approx. 20ppm* |
| BLACK TEXT A4 (Normal) | 15ipm (ISO24734) |
| COLOUR TEXT A4 (Normal) | 5.5ipm (ISO24734) |
| PHOTO 4"x6" (10x15cm) (DRAFT)^ | Approx. 50 sec * + |

Print Speed Data Printout Patterns The thumbnail images below show the printout patterns used to determine print speed specifications.

**"Second" rating refers to the time taken to print one page. The computer environment we test under is as follows: CPU: Pentium 4, 2.4GHz; RAM: 512MB; OS: Windows XP professional; Interface/Connectivity: USB2.0 HighSpeed; SOFTWARE: Word XP/PhotoShop7.0; PAPER: Epson Premium Glossy Photo Paper or Plain Paper

+ When printed on Epson Premium Glossy Photo Paper

PAPER HANDLING

| | |
|----------------------------|--|
| PAPER FEED METHOD | Friction feed with paper feeder and automatic document feeder |
| PAPER SIZES | |
| | A4, A5, B5, A6, Legal, 13 x 18cm, 10 x 15cm, 9 x 13cm, 13 x 20cm, 20 x 25cm Envelopes: C6, No 10, DL |
| PAPER HOLD CAPACITY | |
| | Paper Tray input capacity: 120 sheets, A4 Plain paper (64g/m2) *True BorderFree™ printing is available for the following media sizes: 4" x 6", 5" x 7" and A4. Media types recommended : Premium Glossy Photo paper A4, 4" x 6" and 5" x 7", Matte Paper - Heavyweight. BorderFree prints are media dependent. |

Scanner

| | |
|---------------------|---|
| SCANNER TYPE | A4 Flatbed colour image scanner |
| DOCUMENT SIZE | Up to A4 |
| PIXEL DEPTH Input | 48bits (16bits/colour) / output 24bits (8bits/colour) |
| SCANNING RESOLUTION | 1200 x 2400dpi |
| MONO SCAN SPEED | 1200dpi 3.8msec/line |
| COLOUR SCAN SPEED | 1200dpi 11.2msec/line |

Copy Function

| | |
|-----------------------------------|--|
| COPY SPEED | |
| COPY SPEED BLACK TEXT MEMO (A4)+ | Approx. 38cpm (Draft) |
| COPY SPEED COLOUR TEXT MEMO (A4)+ | Approx. 13cpm (Draft) |
| REDUCTION/ENLARGEMENT | |
| COPY MODES | Auto Fit Function Standard, BorderFree |

FAX

| | |
|-----------------------|--|
| TYPE | Colour and mono support |
| LINES | PSTN (general phone lines) |
| TRANSMISSION SPEED | Up to 33.6kbs (approx. 3 secs / page) |
| SPEED DIAL | Up to 60 Names & Numbers |
| MEMORY | Up to 180 pages (ITU-T No.1 chart) |
| FAX RESOLUTION | Standard (200x100), Fine (200x200), Photo (200x200 with error diffusion) |
| ERROR CORRECTION MODE | CCIT/ITU Group3 fax with Error Correction Mode |
| RING DETECTION | Yes Duet |
| PC FAX | Yes |
| AUTO REDIAL | Yes |
| GROUP DIAL | Yes |
| BROADCAST FAX | Yes (mono only) |

AUTOMATIC DOCUMENT FEEDER FUNCTION

| | |
|--------------------------|-----------------------------------|
| MAXIMUM DOCUMENT SIZE | A4 |
| PAPER TYPES SUPPORTED | Plain paper 75-95g/m2 |
| PAPER CAPACITY | Up to 30 pages (Plain paper only) |
| OPERATING SYSTEMS | |

| | |
|---------------------------|---|
| PRINTER DRIVERS* Windows® | 7/7x64/Vista/Vista64/XP/XP64/2000, Mac® OS 10.4.11 or later with USB* |
|---------------------------|---|

* Drivers if available are downloadable from Tech Epson

ELECTRICAL SPECIFICATIONS

| | |
|--------------------------|--|
| RATED VOLTAGE | AC 220 ~ 240V |
| RATED FREQUENCY | 50 ~ 60Hz |
| POWER CONSUMPTION | |
| | Approx. 15W (Standalone copying ISO/IEC 24712) |
| | Approx 4W (Sleep Mode) |

NOISE LEVEL

| | |
|---------------|--|
| NOISE LEVEL # | 5.3B (ISO7779 Pattern with PGPP /Photo RPM mode) 39db (ISO9296) |
|---------------|--|

According to ISO7779 Pattern with Premium Glossy Photo Paper / Photo RPM mode.

INTERFACES

| | |
|--------------|--|
| CONNECTIVITY | High-Speed USB — Compatible with the USB 2.0 Specification. (cable included) |
|--------------|--|

MOBILE DEVICE PRINTING

| | |
|--|---|
| | Yes - Epson iPrint (wireless photo printing from Apple® iPod Touch®, iPhone® & iPad™ - downloadable from Apple iTunes® Store) |
|--|---|

NETWORKING

| | |
|--|---|
| | 10-Base-T, 100 Base-TX Ethernet (cable included) 802.11b/g/n Wi-Fi |
|--|---|

LCD SCREEN

| | |
|--|--------------|
| | Line Display |
|--|--------------|

PRINTER SOFTWARE (AVAILABLE ON CD-ROM ONLY)

| | |
|-----------------|--|
| SOFTWARE TOOLS* | Epson Event Manager (with Scan 2.0, Email 1.1)PC FAX Software Epson Easy Photo Print, Epson Web-To-Page, Online Guide |
|-----------------|--|

WARRANTY

| | | |
|--|-------------------------------------|----------|
| | 12 months return to base | Standard |
| | Optional Additional 2 Year Warranty | 2YW525 |
| | Epson Warranty | |

PRODUCT DIMENSIONS

| | |
|--|-----------------------------------|
| | 460mm (W) x 403mm (D) x 235mm (H) |
|--|-----------------------------------|

WEIGHT

| | |
|--|-------|
| | 7.4kg |
|--|-------|

LIGHTFASTNESS

| | |
|----------------|--|
| LIGHTFASTNESS# | 120 years on Epson Matte Paper Heavyweight |
|----------------|--|

LIGHTFASTNESS TEST CRITERIA (INDOOR DISPLAY CONDITIONS)

| | |
|--------------------------|--|
| LIGHT SOURCE | Fluorescent light |
| INTENSITY | 70k lux |
| TEMPERATURE | 24°C |
| HUMIDITY | 60% RH |
| GLASS MOUNT | 2mm, soda lime |
| FADE CRITERIA | Pure YMC 30% loss at OD=1 |
| DISPLAY LIFE CALCULATION | Total illuminance/(500 lux x 10 hours x 365 days = 1 year) Tests developed and conducted by Epson under fluorescent light (indoor display condition) with glass mount. The data is calculated by Epson's accelerated test of prints on specialty media. |

Data is calculated using accelerated simulation of fading under indoor preservation conditions including fluorescent light indoor display. Temperature, humidity and some atmospheric gases may also affect the rate of fading. The estimated lightfastness period does not indicate the colour changing or the durability of the paper itself. Epson recommends that your prints be stored in a photo album (or plastic photo storage box) in acid free, archival sleeves commonly available from most camera shops.

INK CARTRIDGES & YIELDS

| | |
|--|--|
| STANDARD CAPACITY INK CARTRIDGES | 133 Black |
| HIGH CAPACITY INK CARTRIDGES | 138 Black, 138 Cyan, 138 Magenta, 138 Yellow |
| EXTRA HIGH CAPACITY INK CARTRIDGES | 140 Cyan, 140 Magenta, 140 Yellow |
| STANDARD CAPACITY BLACK INK YIELD^^ | Approx. 445 pages with 2 ink cartridges |
| HIGH CAPACITY BLACK INK YIELD^^ | Approx. 740 pages with 2 ink cartridges |
| HIGH CAPACITY COLOUR COMPOSITE INK YIELD^^ | Approx. 480 pages |
| EXTRA HIGH CAPACITY COLOUR COMPOSITE INK YIELD^^ | Approx. 740 pages |

^ Print speed (PPM) when printed on A4 plain paper in the fastest mode. 10x15cm photo print speed when printed on Epson Premium Glossy Photo Paper borderless in draft mode. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.

+ Copy speed when printed on plain paper in the fastest mode. Copy speed may vary depending on copy mode, document complexity, type of paper used and number of copies.

^^ According to ISO/IEC24711 and 24712 test suite. [Click here for details on ISO testing. \(PDF\)](#)

† Maximum pages per minute (PPM) are measured after first page with text patterns in Draft Mode on plain paper. ISO ppm is based on ISO/IEC 24734. Black and colour print speeds are determined in default, single-side mode, in accordance with ISO/IEC 24734. Actual print times will vary based on system configuration, software, and page complexity. See www.epson.com.au/printspeed for details, including complete ISO reports.

*Some applications and/or functions, like two-sided printing, may not be supported by Mac®



Better Products for a Better Future™
www.epson.com.au/company/environment



Epson Australia, Inc.
3 Talavera Rd,
North Ryde, NSW, 2113

www.epson.com.au
www.epson.co.nz