



## Epson TM-P60II (Receipt / Label)

**Tough and robust, the TM-P60II offers the fastest printing speed in its class**

Industry-leading operational battery life up to 46 hours

4 foot drop rating and IP54 environmental certified

Supports 802.11 a/b/g/n with 2.4GHz/5GHz compatibility, Bluetooth® 2.1 + EDR and NFC

Paper-saving options

Print width up to 54mm on standard 58mm media

Zebra® emulation available

## Great features for mobile printing

The TM-P60II has all the features you need to print receipts or labels anywhere, anytime. Tough and robust, it offers the fastest printing in its class with speeds up to 100mm/second, an industry-leading battery life, flexible connectivity, a rugged design to ensure reliability in even the harshest environments.

## Best-in-class battery life

To ensure uninterrupted service to your customers, Epson TM-P60II features an industry-leading operational battery life of up to 27 hours with 802.11 models and up to 46 hours with Bluetooth models.

## Multi-platform printing made easy

With Epson's unique ePOS-Print technology, the TM-P60II can print directly from any mobile devices running an iOS, Android or Windows operating system with a WiFi or Bluetooth connection, using a HTML5 browser or native application. This provides an easy and smart solution for today's mobile printing requirement.

## Compatible and ready to go

The TM-P60II wireless printer is compatible with today's best-of-breed POS systems and the latest industry-standard wireless security protocols. The printer supports NFC, 802/11a/b/g/n with 2.4GHz / 5GHz compatibility or Bluetooth®2.1 + EDR. It also comes complete with ESC/POS®, OPOS, JavaPOS and Windows® drivers which means your current applications are instantly compatible.

## Reduce your paper costs

With the TM-P60II paper-saving options, you can reduce your paper usage by up to 23%. The paper-saving settings are easy to use without changing your application and do not affect print quality, readability and font size.

## Backed by the leader

The TM-P60II features the quality and reliability that Epson is known for, a low total cost of ownership and is backed by our leading service and support programs.

Product Specifications	
PRINT METHOD	Thermal line printing
PRINT SPEED (MAX.)	Receipt mode 100mm/sec, label mode 80mm/sec; peeler mode 40mm/sec
DOT/LINE	420/432 dots
FONT	Font A 12 x 24, new Font B 10 x 24, new Font C 8 x 16
COLUMN CAPACITY	58mm paper, Font A/B/C, 35/42/52 columns; 60mm paper, Font A/B/C, 36/43/54 columns
CHARACTER SIZE	1.5 x 3.0 / 1.25 x 3.0 / 1.0 x 2.0 mm (W x H)
Character set	95 Alphanumeric, 48 International, 128 x 10 Graphic
Barcode	1D: EAN-8, EAN-13, UPC-A, UPC-E, JAN13, JAN8, Code 39, Code 93, Code 128, ITF, CODEBAR, GS1-128, GS1 DataBar, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded 2D: QR Code, Maxi Code, PDF417, Composite, Data Matrix, RSS/GS1 and Aztec
Characters per inch	17/20/25 cpi
PAPER WIDTH	Paper or labels, 58mm or 60mm width (receipt version) Paper or labels, 30–60mm (label version)
PAPER DIAMETER (MAX.)	51mm
RELIABILITY	10 million printing lines; 500,000 autocutter (receipt version)
INTERFACE	802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 2.1 + EDR, NFC
SUPPORTED MOBILE	WiFi (802.11): iOS, Android and Windows
OPERATING SYSTEMS	(Security Level WEP, WPA, WPA2-Enterprise) Bluetooth: iOS, Android and Windows
AUTOCUTTER	Partial cut, left uncut (receipt version)
PEELER	Automatic label removal from backing (label version)
AUDIBLE ALERT	Programmable buzzer
SENSORS	Paper out (receipt and label versions) Gap, black mark, label taken (label version)
LED INDICATORS	
Green LED	Power (ON=Power on, OFF=Power off)
Orange LED	Only shown when power is ON. Error, Paper end, Cover open, Battery level low (printer does not operate)
Blue LEDs	Four battery level indicators: 3 LED ON = approx. 100%–60% 2 LED ON = approx. 60%–20% 1 LED ON = approx. 20%–10% 1 LED Flashing = approx. 10%–1%
SOFTWARE	TM-P60II Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P60II Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page
POWER	Custom Lithium-Ion battery pack, AC adapter (option)
Charging	AC adapter (2.5 hours to full charge), custom quad bay charger (2.5 hours to full charge)
BATTERY LIFE	Up to 27 hours with 802.11n, up to 46 hours with Bluetooth 2.1 + EDR*
OPERATING TEMPERATURE	0° C to 45° C
DROP RATING	4 feet
OVERALL DIMENSIONS	4.05" x 6.25" x 2.55" (103 x 159 x 65 mm) (W x D x H)
WEIGHT	Receipt version 1.4 lbs (630g) with battery, belt clip Label version 1.3 lbs (600g) with battery, belt clip
COLOUR	Epson Black (EBCK)
WARRANTY	Two year standard warranty
WHAT'S IN THE BOX	P60II, Battery (Model: OT-BY60II), Roll paper (for checking initial movement of the printer), User's manual, USB cable, Belt clip (already attached to printer), 58mm spacer (already attached to printer)
ACCESSORIES (OPTIONAL)	Battery (OT-BY60II), Quad Charger (OT-CH60II), Power Supply (PS-11), Shoulder Strap and Padded Case (AB1370EPI)

Visit [www.epson.com.au/POS](http://www.epson.com.au/POS)

## Better Products for a Better Future



Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

**EPSON AUSTRALIA**  
3 Talavera Road  
North Ryde NSW 2113  
Tel: (02) 8899 3666  
[www.epson.com.au](http://www.epson.com.au)

**EPSON NEW ZEALAND**  
Level 2 7-9 Fanshawe Street  
Auckland, 1010  
Tel: 0800 443 478  
[www.epson.co.nz](http://www.epson.co.nz)

ABN 91 002 625 783  
05/16

**Epson CoverPlus**  
Fast. Reliable. Professional

**EPSON**  
EXCEED YOUR VISION